



920 Second Ave., Coraopolis, PA 15108
 (800) 670-5767 * FAX (412) 299-6499

TECHNICAL BULLETIN

'COLOR-RITE' PAINT

PPG TrueFinish
 Industrial Coatings

SPECTRACRON 300 SERIES 2K POLYURETHANE ENAMEL

DESCRIPTION:

SPECTRACRON 300 SERIES 2K POLYURETHANE ENAMEL is a 2-component polyurethane with excellent exterior durability. It is recommended for industrial use on pretreated or primed metal surfaces. Suitable applications include various metal fabrications castings, agricultural and construction equipment.

HIGHLIGHTS:

- ◇ Excellent color and gloss retention
- ◇ Available in wide range of colors and gloss
- ◇ Excellent mar resistance
- ◇ Contains no heavy metals

TECHNICAL PROPERTIES:

PROPERTY	METHOD	RESULT*
Color		Custom Colors
Gloss @ 60° Angle	ASTM D523	20—90
Pencil Hardness	ASTM D3363	H—2H
Conical Mandrel	ASTM D522	Excellent
Impact Resistance	ASTM D2794	Excellent
Adhesion	ASTM D3359	Excellent
Humidity Resistance—100 Hrs.	ASTM D2247	Excellent
Salt Spray Resistance—250 Hrs.	ASTM B117	Very Good
Chemical Resistance		Very Good
Abrasion Resistance		Very Good
Substrates		CRS, HRS, Alum, Galv

*These results were obtained over iron phosphated CRS panels.

The test results shown are believed to be reliable. However, variances in testing and actual field conditions may alter the results. There is no expressed or implied warranty on the test data.